



3 IN 1, CLIMATIC TEST CHAMBERS FOR STABILITY TESTS

MODEL, CM-0/6760m and 2x CM-0/11050m

GENERAL:

The **space** to locate new equipment is one of the elements to be taken into account for a correct configuration of the climatic chambers. If the building is old, the existing space for the equipment is reduced, or if the building is new, it is necessary to correctly plan the position of each piece of equipment to be installed in order to optimise the space as much as possible. To this end, the technical-commercial department of **DYCOMETAL** analyses the best possible solutions in order to optimise the existing space to the maximum and to be able to offer the client the best solution with the greatest possible volume.

For the configuration of the 3 chambers, **CM-0/6760m** and **2x CM-0/11050m**, for pharmaceutical stability, the best possible configuration was analysed in detail, building the 3 chambers in a single structure so that the space occupied by the equipment could be reduced as much as possible. The high ceiling allows the products to be tested to be stored more vertically, thus facilitating a greater storage capacity in the existing space and under different stability conditions.



DYCOMETAL EQUIPOS DE C.C., S.L.

C/ De la Ciència, 35-37

08840 - Viladecans (Barcelona) - SPAIN

T: (34) 936 526 610 F: (34) 936 407 607

www.dycometal.com



TECHNICAL FEATURES:

- Volumes:
 - Chamber-1: 6.760 liters.
 - Chamber-2: 11.050 liters.
 - Chamber-3: 11.050 liters.
- Internal dimensions:
 - Chamber-1: 3.800 x 920 x 2.020 mm (H x W x D).
 - Chamber-2: 3.800 x 1.400 x 2.020 mm (H x W x D).
 - Chamber-3: 3.800 x 1.400 x 2.020 mm (H x W x D).
- External dimensions: 3.800 x 4.000 x 2.500 mm (H x W x D).
- Pivoting access doors. Dimensions: 1850 x 590 mm (H x W).
- Temperature range: from +10 °C to +50 °C (each chamber).
- Humidity range: 50 % to 80 % R.H. (each chamber).
- Observation window in each door.
- Interior: Stainless steel.
- Internal sanitary profile.
- Access-port: 3x 80 mm Ø.
- Control via 4,3" colour touch screen.
- Ethernet communication port
- Independent sensor for connecting with the customer data recorder.
- Remote cooling group prepared for outdoor conditions.
- CE mark.



DYCOMETAL EQUIPOS DE C.C., S.L.

C/ De la Ciència, 35-37

08840 - Viladecans (Barcelona) - SPAIN

T: (34) 936 526 610 F: (34) 936 407 607

www.dycometal.com

